



MOUNTFROST

COMMERCIAL REFRIGERATION EQUIPMENT



Where Innovation Meets
Freshness

About Mount Frost

Mount Frost is a trusted name in the world of commercial refrigeration, dedicated to delivering superior cooling solutions for businesses across industries. We specialize in designing and manufacturing high-quality refrigeration equipment that ensures freshness, reliability, and energy efficiency. From retail and hospitality to industrial applications, our products are engineered to cater to the specific needs of each sector, maintaining optimal performance even in demanding environments.

At Mount Frost, innovation drives everything we do. Our state-of-the-art technology, combined with robust construction, guarantees long-lasting performance and minimal maintenance. We take pride in offering a diverse range of refrigeration solutions tailored to help your business thrive while contributing to a sustainable future.

With a commitment to excellence and customer satisfaction, Mount Frost is not just a provider but a partner you can rely on. Experience the difference with refrigeration solutions built to keep your business cool and efficient.





Faster cooling



Silent operation



Eco-friendly



Pan India network for quick services & on call assistance



In-situ power-saving PUF insulation



Food grade SS tank and body



Sturdy compressor and trouble free operation

WATER COOLERS

S. No	Model No	Power Consumption	Refrigeration	Power Supply	Rate of Cooling	Storage Capacity	Body and Tank
1	MF22/20	350w	R-134A (Non CFC)	230 V AC, 59Hz, 1phase AC	20LTR	22LTR	Full Stainless Steel
2	MF40/80	575w	R-134A (Non CFC)	230 V AC, 59Hz, 1phase AC	40LTR	80LTR	Full Stainless Steel
3	MF80/150	950w	R-134A (Non CFC)	230 V AC, 59Hz, 1phase AC	80LTR	150LTR	Full Stainless Steel
4	MF150/150	1550w	R-134A (Non CFC)	230 V AC, 59Hz, 1phase AC	150LTR	150LTR	Full Stainless Steel
5	MF150/300	1550w	R-134A (Non CFC)	230 V AC, 59Hz, 1phase AC	150LTR	300LTR	Full Stainless Steel
6	MF200/500	2000w	R-134A (Non CFC)	230 V AC, 59Hz, 1phase AC	200LTR	500LTR	Full Stainless Steel
7	MF300/1000	2000w	R-134A (Non CFC)	230 V AC, 59Hz, 1phase AC	300LTRFC)	1000LTR	Full Stainless Steel



- Front Heated Glass
- All Side Glass View
- Three Shelf + Base



LED Light Illustration
for Each Shelf



Sliding Door



Bigger Display Area

Different Glass Shapes Available

Curved Glass | Straight Glass
Inclined Glass | Panoramic Glass
Round Show Case

DISPLAY COUNTER

Model No	Shelves	Dimension	Volume (Ltrs)	Temperature Range	Rated Electric Input	Front Glass	Body And Shelf
MFD100	Base + 2	48 x 29 x 48	320	2 - 8°C	850 W	Heated	SS 304
MFD101	Base + 3	48 x 33 x 55	480	2 - 8°C	950 W	Heated	SS 304
MFD102	Base + 3	40 x 27 x 53	320	2 - 8°C	280 W	Heated	SS 304
MFD103	Base + 3	48 x 27 x 53	360	2 - 8°C	320 W	Heated	SS 304
MFD104	Base + 2	48 x 27 x 48	390	2 - 8°C	850 W	Heated	SS 304
MFD105	Base + 2	40 x 27 x 48	300	2 - 8°C	280 W	Heated	SS 304
MFD106	Base + 2	48 x 27 x 48	380	2 - 8°C	320 W	Heated	SS 304
MFD107	Base + 3	40 x 27 x 53	350	2 - 8°C	280 W	Heated	SS 304
MFD108	Base + 3	40 x 27 x 53	400	2 - 8°C	320 W	Heated	SS 304
MFD109	Base + 3	48 x 32 x 57	500	2 - 8°C	490 W	Heated	SS 304
MFD110	Base + 4	27 x 27 x 69	400	2 - 8°C	480 W	Heated	SS 304
MFD111	4 Shelves	28 x 28 x 71	468	2 - 8°C	280 W	Heated	SS 304



Energy Efficient Compressor



Upto 40% Electricity Saving



Door Lock For Restricted Accessibility



Eco-Friendly Gas Refrigerant



Longer Cooling Retention.



Safety Compliant



Sunken Handle For Safer Operation



Tropicalized Machines



Compact Design

REFRIGERATOR/FREEZER TWO DOOR FOUR DOOR

Description	MFR2/112 MFF2/112	MFR4/113 MFF4/113	MFR2/114 MFF2/114	MFR4/115 MFF4/115	MFR2/116 MFF2/116	MFR4/117 MFF4/116	MFR4/118 MFF4/118
Capacity (Ltrs)	600	1100	655	1400	655	1400	1400
Temperature Range	(0 to +12 c) (-20 to -7c)	(0 to +12 c) (-20 to -7c)	(0 to +12 c) (-20 to -7c)	(0 to +12 c) (-20 to -7c)	(0 to +12 c) (-20 to -7c)	(0 to +12 c) (-20 to -7c)	(0 to +12 c) (-20 to -7c)
No Of Doors	2	4	2	4	2	4	4
Type Of Doors (Int/Ext)	SS-201/201	SS-201/201	SS-304/201	SS-304/201	SS-304/201	SS-304/201	SS-201/201
Shelves Qty	3	6	3	6	4	8	8
Light	No	No	Yes	Yes	Yes	Yes	Yes
Refrigerant Gas (Type/Charge)	(R134a/250g) (R134a/330g)	(R134a/280g) (R134a/320g)	(R134a/250g) (R134a/290g)	(R134a/300g) (R134a/440g)	(R290/90g) (R290/115g)	(R290/120g) (R290/120g)	(R290/120g) (R290/120g)
Voltage & Frequency (V- Hz)	220-240V/ 50Hz	220-240V/ 50Hz	220-240V/ 50Hz	220-240V/ 50Hz	220-240V/ 50Hz	220-240V/ 50Hz	220-240V/50Hz
Power (Watts)	270	358	322	524	250	600	600
Current (Amps)	2.0	2.5	4.5	4.5	13	3.3	3.3
Defrost	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Temperature Display LED	Yes	Yes	Yes	Yes	Yes	Yes	Yes
External Dimension (W x Dx H) mm	680 x 755 x 1965	1220 x 755 x 1965	700 x 820 x 2050	1400 x 820 x 205	700 x 880 x 2043	1400 x 880 x 2043	1400 x 880 x 2043
Gross Weight (Kg)	110	160	150	220	130	210	210



**Energy Efficient
Compressor**



**Upto 40%
Electricity Saving**



**Door Lock For
Restricted
Accessibility**



**Eco-Friendly
Gas Refrigerant**



**Longer Cooling
Retention.**




**Safety
Compliant**



**Sunken Handle
For Safer Operation**



**Tropicalized
Machines**



Compact Design

COLD ROOMS

Model No.	Refrigeration / Capacity BTU / Hr.	Temp. Range	Loading Temp	Max. Loading (kgs./Day)	Max. Room Volume with 8' Ht. (CFT)	Max. Room Area (SQ. FT.)	Power* (SQ. FT.) (kw)	Power Supply (V / Ph / Hz)	Defrosting
MFC/123	8000	2 to 6	30	280	512	64	1.6	230V/1Ph/50hz	Off-cycle
MFC/124	12000	2 to 6	30	540	960	120	2	230/1/51	Off-cycle
MFC/125	15000	2 to 6	30	770	1360	170	2.5	230/1/52	Off-cycle
MFC/126	19000	2 to 6	30	1000	1800	225	3	400/3/50	Off-cycle
MFC/127	21000	2 to 6	30	1200	2080	260	3.4	400/3/50	Off-cycle
MFC/128	30000	2 to 6	30	2200	3800	475	5.3	400/3/50	Off-cycle
MFC/129	41000	2 to 6	30	2600	4520	565	5.7	400/3/50	Off-cycle
MFCF/130	6000	(-18 to -22)	-10	280	512	64	2	400/3/50	Electric
MFCF/131	8000	(-18 to -22)	-10	425	750	90	2.8	400/3/50	Electric
MFCF/132	10000	(-18 to -22)	-10	570	1000	125	3.4	400/3/50	Electric
MFCF/133	14000	(-18 to -22)	-10	900	1600	200	4.3	400/3/50	Electric
MFC/134	18000	(-18 to -22)	-10	1400	2520	315	6.2	400/3/50	Electric
MFC/135	23000	(-18 to -22)	-10	2000	3520	440	8.1	400/3/50	Electric

OUR NETWORK



MOUNTFROST

+91 8076066301, 9911445055, 9212270950

mountfrost471@gmail.com

www.mountfrost.in

A-50, Third Floor, Dashrathpuri, Dabri, Palam Road, New Delhi-110045